



www.worldtradedisplay.com

DISPLAY DIGITAL SOLUTIONS

PCAP All in One Touch Solutions - NUBY Wallmount Series



Display & Digital Signage Solutions

Wide Range, Easy & Accurate

Make your choice from various interactive display, videowall & digital signage discovering the multi-touch technology.

All in One Solutions

WTD solutions available also with Android/PC included, to satisfy the space & performances requests in only one item.

Common Scenarios

Innovative communicative creativity, conceived & designed to meet different needs in the outdoor/indoor environments.

Benefits

Wide range of dimensions designed to cover all the most common usage scenarios in the professional markets, where it's also required high brightness or protection against high temperatures, thanks to our wide range of products such as videowall, open frame, touch display & digital signage solutions.

FEATURES	REMARKS	SPECIFICATIONS
Display	Type of product	Digital Signage
	Panel Size available	32"/ 43"/ 49"/ 55"/ 65"
	Active Area	32" 698 x 393 mm 16:9 1920 x 1080
	Aspect Ratio	43" 941 x 529 mm 16:9 1920 x 1080
	Resolution	49" 1073 x 603 mm 16:9 1920 x 1080
		55" 1208 x 679 mm 16:9 1920 x 1080
		65" 1430 x 805 mm 16:9 1920 x 1080
	Brightness	400/ 500 cd/m2 (Range)
	Colors	16,7 million
	Viewing Angle	Horizontal (left/right): 178° Vertical (up/down): 178°
	Response Time (Pixel)	8/ 5 ms (Range)
	Contrast Ratio	1000:1/ 5000:1 (Range)
	Input Video Format	RGB Analog/ DVI-D /HDMI
	Input Video Signal	VGA/ HDMI
High 4K Resolution	On Demand	
High Brightness	On Demand	
Double Display	No	
PC Functions	CPU	i3/ i5/ i7/ Over...
	RAM	4/ 8/ 16 Gb
	SSD	64/ 128/ 256 Gb
	Connections	Wi-Fi x1, RJ45 x1
	Media Player	Yes
	System OS	Windows/ Linux/ Other
	Android	5.1.1 Version/ Over...
	OPS Module Slot	No
	Other Function	On Request
Touch Functions	Technology	PCAP
	Point	10
	Interface	USB
	Surface Hardness	≥7 H
	Resolution	4096x4096
	Response Time	<15/ <10 ms
	Input Method	Finger or Capacitive Pen
Connectivity	Interface	USB
	Speaker	-
Function Conditions	Relative Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
	Temperature Range	Operating: 0° ~ 40°C Storage: -20° ~ 60°C
	Screen Position	Landscape (Default) or Portrait
Mechanical	Installation (VESA)	400x400 Side
	Sheel Material	Alluminium frame, tempered glass face & cold-rolled sheet body
	Glass	Tempered Glass
	Enclosure Color	Silver Border and Black Body
Power & Accessory	Power Supply	AC 100-240V Input DC 12V, 24V 50/60 Hz
	Power Cons. (Max)	44W/ 56W (Range)
	Cables	Power Supply with Cable Schuko
	Input Connector	AC: Cable Power Schuko

FEATURES	REMARKS	SPECIFICATIONS
Packaging	Dimension (Net) (L x W x H)	32" 754 x 62 x 449 mm 19.1 Kg
	Weight (Single)	43" 997 x 62 x 585 mm 25.1 Kg 49" 1169 x 62 x 659 mm 27.2 Kg 55" 1264 x 62 x 735 mm 31.55 Kg 65" 1493 x 112 x 868 mm 41 Kg
	Carton Dimension (L x W x H)	On Demand
Policy	Warranty	2 Years (Panel 1 Year)
	Agency Approval	CE - FCC - CCC
Other/ Upgrade	Extra Time Warranty	Please contact us if you need more informations
	Different Version	Available also with High Brightness and other kind od panel Special mechanical design
	Notes	Panel specification above comes from typical panel and for reference only, please contact our sales for the final confirmation, if needed.