

















www.worldtradedisplay.com

MIRROR DIGITAL SIGNAGE SOLUTIONS

PCAP All in One Touch Solutions - FLEXI Wallmount Series



Display & Digital Signage Solutions

Wide Range, Easy & Accurate

Make your choice from various interactive display, videowall & digital signage discovering the multi-touch technology.

All in One Solutions

WTD solutions available also with Android/PC included, to satisfy the space & performances requests in only one item.

Common Scenarios

Innovative communicative creativity, conceived & designed to meet different needs in the outdoor/indoor environments.

Benefits

Wide range of dimensions designed to cover all the most common usage scenarios in the professional markets, where it's also required high brightness or protection against high temperatures, thanks to our wide range of products such as videowall, open frame, touch display & digital signage solutions.



marketing@worldtradedisplay.com



TECHNICAL SPECIFICATION

DIGITAL SIGNAGE SOLUTIONS | PCAP

FLEXI WALLMOUNT SERIES

FEATURES	REMARKS	SPECIFICATIONS
Display	Type of product	Digital Signage
	Panel Size available	43"/ 49"/ 55"
	Active Area	43" 941 x 529 mm 16:9 1920 x 1080
	Aspect Ratio Resolution	49" 1077 x 608 mm 16:9 1920 x 1080 55" 1209 x 680 mm 16:9 1920 x 1080
	Brightness	1000 cd/m2
	Colors	16,7 million
	Viewing Angle	Horizontal (left/right): 178° Vertical (up/down): 178°
	Response Time (Pixel)	8/ 5 ms (Range)
	Contrast Ratio	1000:1
	Input Video Format	RGB Analog/ HDMI
	Input Video Signal	VGA/ HDMI
	High 4K Resolution	On Demand
	High Brightness	On Demand
	Double Display	No
PC Functions	CPU	i3/ i5/ i7/ Over
	RAM	4/ 8/ 16 Gb
	SSD	64/ 128/ 256 Gb
	Connections	Wi-Fi x1, RJ45 x1
	Media Player	Yes
	System OS	Windows/ Linux/ Other
	Android	7.1 Version/ Over
	OPS Module Slot	No
	Other Function	On Request
Touch Functions	Technology	PCAP
roden ranctions	Point	10
	Interface	USB
	Surface Hardness	≥7 H
	Resolution	4096x4096
	Response Time	<15/ <10 ms
	Input Method	Finger or Capacitive Pen
Connectivity	Interface	USB
Connectivity	Speaker	Built-In 2*10W
Function Conditions	Relative Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
r unction conditions	Temperature Range	Operating: 0° ~ 40°C Storage: -20° ~ 60°C
	Screen Position	Landscape (Default) or Portrait
Mechanical	Installation (VESA)	400x400 Side
	Sheel Material	Alluminium frame, tempered glass face & cold-rolled sheet body
	Glass	Mirror Glass
	Enclosure Color	Silver Border and Black Body
Power & Accessory	Power Supply	AC 100-240V Input DC 12V, 24V 50/60 Hz
/	Power Cons. (Max)	100/120 W (Range)
	Cables	Power Supply with Cable Schuko
	Input Connector	AC: Cable Power Schuko



TECHNICAL SPECIFICATION

DIGITAL SIGNAGE SOLUTIONS | PCAP

FLEXI WALLMOUNT SERIES

FEATURES	REMARKS	SPECIFICATIONS
Packaging	Dimension (Net) (L x W x H) Weight (Single)	43" 1011 x 77 x 599 mm 28 Kg 49" 1076 x 77 x 671 mm 32 Kg 55" 1284 x 81 x 756 mm 38 Kg
	Carton Dimension (L x W x H)	On Demand
Policy	Warranty	2 Years (Panel 1 Year)
	Agency Approval	CE - FCC - CCC
Other/ Upgrade	Extra Time Warranty	Please contact us if you need more informations
	Different Version	Available also with High Brightness and other kind od panel
		Special mechanical design
	Notes	Panel specification above comes from typical panel and for reference only, please contact our sales for the final confirmation, if needed.

World Trade Display reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. WTD, World Trade Display it's a registered trademarks of World Trade Display Srl. All other trademarks are the property of their respective owners. Copyright World Trade Display Srl. All rights reserved.